

STANDARD DEPARTURE
CHART - INSTRUMENT
(SID)

USHARAL TOWER 118.1


TRANSITION ALTITUDE
10000 FT

AGAKA 3A,
NESUN 1A

USHARAL
RWY 09

DIST IN NM
ALT, ELEV IN FT
BRG ARE MAGNETIC
VAR 5°E

ALT/HEIGHT CONVERSION
QNH (QFE)
2000 (705ft - 215 m)



WARNING:
Min. PDG 6%

AGAKA 3A
After take-off climb straight ahead to 2000 or above, turn LEFT on track 326° until intercept bearing 186° \searrow , then proceed on track 006° to AGAKA (N463544 E0805503).

NESUN 1A
After take-off climb straight ahead to 2000 or above, turn LEFT to NDB \searrow , after crossing NDB \searrow proceed on track 239° to NESUN (N460123 E0801738).

AGAKA
46°35'44"N
080°55'03"E
FL120-FL140

UAD8
190 FL
GND

AGAKA 3A

USHARAL
NDB 380.0
 \searrow - - -
46°11'36"N
080°48'11"E

1965

2723

2126


2291

1505

2000
UAR177
7500 FT MSL
GND

NESUN
46°01'23"N
080°17'38"E
FL120-FL140

SCALE 1:400000



Change: ALT/HEIGHT CONVERSION tab., TWR freq.

THIS PAGE INTENTIONALLY LEFT BLANK