

TABULAR DESCRIPTION

ARSUL 1P											
Serial Number	Path Descriptor	Waypoint Identifier	Fly - over	Course °M(°T)	Magnetic Variation(°)	Distance NM	Turn Direction	Altitude FT	Speed KT	VPA (°)	Navigation Specification
10	CA	-	-	101(106.2)	+5.5	-	-	@2700	-	-	RNAV 1
20	DF	II160	-	-	+5.5	-	L	-8000	-240	-	RNAV 1
30	TF	II161	-	281(286.4)	+5.5	11.5	-	+9000	-	-	RNAV 1
40	TF	II163	-	281(286.2)	+5.5	17.7	-	+FL130	-	2.5	RNAV 1
50	TF	ARSUL	-	207(212.4)	+5.5	16.0	L	-	-	-	RNAV 1

EDIBA 1E											
Serial Number	Path Descriptor	Waypoint Identifier	Fly - over	Course °M(°T)	Magnetic Variation(°)	Distance NM	Turn Direction	Altitude FT	Speed KT	VPA (°)	Navigation Specification
10	CA	-	-	101(106.2)	+5.5	-	-	@2700	-	-	RNAV 1
20	DF	II160	-	-	+5.5	-	L	-8000	-240	-	RNAV 1
30	TF	II161	-	281(286.4)	+5.5	11.5	-	+9000	-	-	RNAV 1
40	TF	II163	-	281(286.2)	+5.5	17.7	-	+FL130	-	2.5	RNAV 1
50	TF	II164	-	294(299.1)	+5.5	11.0	R	+FL140	-	0.9	RNAV 1
60	TF	EDIBA	-	266(271.6)	+5.5	18.2	L	-	-	-	RNAV 1

EDIBA 1P											
Serial Number	Path Descriptor	Waypoint Identifier	Fly - over	Course °M(°T)	Magnetic Variation(°)	Distance NM	Turn Direction	Altitude FT	Speed KT	VPA (°)	Navigation Specification
10	CA	-	-	101(106.2)	+5.5	-	-	@2700	-	-	RNAV 1
20	DF	II160	-	-	+5.5	-	L	-8000	-240	-	RNAV 1
30	TF	II161	-	281(286.4)	+5.5	11.5	-	+9000	-	-	RNAV 1
40	TF	II163	-	281(286.2)	+5.5	17.7	-	+FL130	-	2.5	RNAV 1
50	TF	II167	-	235(240.6)	+5.5	16.0	L	+FL140	-	0.6	RNAV 1
60	TF	EDIBA	-	309(314.6)	+5.5	19.5	R	-	-	-	RNAV 1

LARBA 1E											
Serial Number	Path Descriptor	Waypoint Identifier	Fly - over	Course °M(°T)	Magnetic Variation(°)	Distance NM	Turn Direction	Altitude FT	Speed KT	VPA (°)	Navigation Specification
10	CA	-	-	101(106.2)	+5.5	-	-	@2700	-	-	RNAV 1
20	DF	II160	-	-	+5.5	-	L	-8000	-240	-	RNAV 1
30	TF	II161	-	281(286.4)	+5.5	11.5	-	+9000	-	-	RNAV 1
40	TF	II163	-	281(286.2)	+5.5	17.7	-	+FL130	-	2.5	RNAV 1
50	TF	II164	-	294(299.1)	+5.5	11.0	R	+FL140	-	0.9	RNAV 1
60	TF	LARBA	-	293(298.9)	+5.5	9.3	-	-	-	-	RNAV 1

MAGOL 1E											
Serial Number	Path Descriptor	Waypoint Identifier	Fly - over	Course °M(°T)	Magnetic Variation(°)	Distance NM	Turn Direction	Altitude FT	Speed KT	VPA (°)	Navigation Specification
10	CA	-	-	101(106.2)	+5.5	-	-	@2700	-	-	RNAV 1
20	DF	II160	-	-	+5.5	-	L	-8000	-240	-	RNAV 1
30	TF	II161	-	281(286.4)	+5.5	11.5	-	+9000	-	-	RNAV 1
40	TF	II163	-	281(286.2)	+5.5	17.7	-	+FL130	-	-	RNAV 1
50	TF	II165	-	327(332.9)	+5.5	8.0	R	+FL140	-	2.3	RNAV 1
60	TF	MAGOL	-	327(332.8)	+5.5	7.9	-	-	-	-	RNAV 1

MIKNO 1E											
Serial Number	Path Descriptor	Waypoint Identifier	Fly - over	Course °M(°T)	Magnetic Variation(°)	Distance NM	Turn Direction	Altitude FT	Speed KT	VPA (°)	Navigation Specification
10	CA	-	-	101(106.2)	+5.5	-	-	@2700	-	-	RNAV 1
20	DF	II160	-	-	+5.5	-	L	-8000	-240	-	RNAV 1
30	TF	II161	-	281(286.4)	+5.5	11.5	-	+9000	-	-	RNAV 1
40	TF	II163	-	281(286.2)	+5.5	17.7	-	+FL130	-	2.5	RNAV 1
50	TF	II167	-	235(240.6)	+5.5	16.0	L	+FL140	-	-	RNAV 1
60	TF	II169	-	223(228.2)	+5.5	16.3	L	+FL140	-	0.3	RNAV 1
70	TF	MIKNO	-	204(209.7)	+5.5	21.6	L	-	-	-	RNAV 1

TONLA 1E											
Serial Number	Path Descriptor	Waypoint Identifier	Fly - over	Course °M(°T)	Magnetic Variation(°)	Distance NM	Turn Direction	Altitude FT	Speed KT	VPA (°)	Navigation Specification
10	CA	-	-	101(106.2)	+5.5	-	-	@2700	-	-	RNAV 1
20	DF	II160	-	-	+5.5	-	L	-8000	-240	-	RNAV 1
30	TF	II161	-	281(286.4)	+5.5	11.5	-	+9000	-	-	RNAV 1
40	TF	II163	-	281(286.2)	+5.5	17.7	-	+FL130	-	2.5	RNAV 1
50	TF	II167	-	235(240.6)	+5.5	16.0	L	+FL140	-	-	RNAV 1
60	TF	II169	-	223(228.2)	+5.5	16.3	L	+FL140	-	0.3	RNAV 1
70	TF	TONLA	-	224(229.3)	+5.5	11.0	-	-	-	-	RNAV 1

WAYPOINT LIST

WPT	COORD	
ARSUL	422600.00N	0685000.00E
DEP	422139.35N	0692940.74E
EDIBA	424519.00N	0682349.00E
II160	423123.34N	0693935.94E
II161	423436.62N	0692440.23E
II163	423931.18N	0690134.42E
II164	424451.31N	0684831.58E
II165	424638.38N	0685637.20E
II167	423137.28N	0684241.25E
II169	422045.45N	0682621.07E
LARBA	424922.00N	0683725.00E
MAGOL	425338.00N	0685144.00E
MIKNO	420200.00N	0681200.00E
TONLA	421334.00N	0681508.00E